

Versatech 1100

Bariatric Low Bed



High performance:

- **1100 lb.** capacity for bariatric use.
- Fall prevention **8 in. low-profile** bed.
- Ultra silent DC motors. **The quietest on the market**, helps maintain a calm and relax environment.
- **Light** weight head and foot boards for ease of use.
- Maintenance friendly with **quick connect** components.
- CSA **certified to Canadian and US standards.**

ROTEC
INTERNATIONAL
ADJUSTABLE BEDS
Brilliantly designed



8 in. low-profile



Width extension



Length extension



Chair position

There are numerous features and options available. Our bed can be customized to meet the specific conditions in each sector of your institution.

DETAILED TECHNICAL DATA

		INCLUDED	OPTIONAL
Central brake system	1 pedal at the foot section	●	
Caster	5 in. double	●	
	5 in. double anti static		●
Head board and foot board	Composite	●	
Side rails	Increased protection (RDRTG2 – 28 x 14)	●	
Patient controls	1 basic remote control	●	
	1 remote control with auto contour feature		●
	2 remote controls with auto contour feature		●
	Controls integrated into head side rails		●
Controls integrated into the head side rails *1	Basic (auto-contour included)	●	
	Complete (Trendelenburg included, outer side)		●
	Light option *2		●
	Nurse call option *2		●
Nurse control	Integrated into the foot board	●	
	With light, electrical CPR, chair position and complete locking function *2		●
Drainage bag holders	Two per side	●	
Battery back-up		●	
Balkan holder		●	
Bumpers at the head section		●	
Support for IV poles	2 (behind the head board)	●	
Trapeze holder		●	
Backrest angle indicator	One per side		●
16 openings for restraint straps		●	
Mattress retainer	Foot	●	
	Side		●
Bed extension	80 in. to 84 in. to 88 in. (no tools required)	●	
Caster covers			●
Composite platform		●	

SPECIFICATIONS

Mattress deck width	36 in. to 54 in.
Mattress deck length	80 in. to 84 in. to 88 in.
Minimum height	8 5/16 in.
Maximum height	32 in.
Load capacity	1100 lb.
Backrest angle	~65°
Footrest angle	~34°
Trendelenburg position	~12°
Under bed clearance	6 in.

OPTIONAL ACCESSORIES

Integrated bed exit alarm
IV pole
Integrated scale
Integrated scale with a bed exit alarm
Bar with trapeze
Night light (LED)
Nurse call with DB-37 *2
Nurse call with ¼ in. cable *2
Bed trolley

WARRANTY INFORMATION

Frame	10 years
Electric motors	2 years
Remote controls and electronic components	2 years
Accessories	1 year

CSA certified to Canadian and U.S. standards
60601-1
60601-1 Amendment 2
60601-2-38-03 and others
Complies with Health Canada and FDA
recommendations regarding entrapment hazards.

Specifications are subject to change without prior notice.

*1 Requires the following option:
Patient control, integrated into side rails.

*2 Certain conditions required.